



Features

- -3dB Bandwidth: 550MHz
- Supply Range: +1.8V to +5.5V
- RON is Typically 6Ω
- Fast Switching Times: t_{ON} 20ns, t_{OFF} 15ns
- Break-Before-Make Switching
- Low Power Consumption (1μA Maximum)
- Rail-to-Rail Input and Output Operation
- Temperature Range: -40°C to +125°C
- Micro Size Packages: SOT23-6

Application

- Wearable Devices
- Battery-Operated Equipment
- Signal Gating, Chopping, Modulation or Demodulation (Modem)
- Portable Computing
- Cell Phones

Description

The RS3SW2157 is a single-pole double-throw (SPDT) analog switch that is designed to operate from 1.8 V to 5.5 V.

The RS3SW2157 device can handle both analog and digital signals. It features high-bandwidth (550MHz) and low on-resistance (6Ω TYP).

Applications include signal gating, chopping, modulation or demodulation (modem), and signal multiplexing for analog-to-digital and digital-to-analog conversion systems.

Ordering Information

Part Number	Package	Description
RS3SW2157T	SOT23-6	2.92mm x 1.62mm


**RSM**

www.raystar-tek.com

RS3SW2157

Low Voltage SPDT Analog Switch

Pin Configuration

**RS3SW2157****SOT23-6, Top View****Table 1. Pin Functions: RS3SW2157**

NAME	PIN	FUNCTION
	SOT23-6	
NO	1	Normally-Open Terminal
GND	2	Ground
NC	3	Normally-Closed Terminal
COM	4	Common Terminal
V+	5	Power Supply
SEL	6	Digital Control Pin

Function Table

LOGIC	NO	NC
0	OFF	ON
1	ON	OFF



Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted) ⁽¹⁾

SYMBOL	PARAMETER		MIN	MAX	UNIT
V ₊	Supply Voltage		-0.3	6.0	V
V _{IN}	Input Voltage ⁽²⁾		-0.3	6.0	
	Analog, Digital Voltage Range		-0.3	(V ₊)+0.3	
	Continuous Current NO, NC, or COM		-100	+100	mA
I _{PEAK}	Peak Current NO, NC, or COM		-150	+150	
θ _{JA}	Package thermal impedance ⁽³⁾	SOT23-6		235	°C/W
T _J	Junction Temperature ⁽⁴⁾		-40	150	°C
T _{stg}	Storage temperature		-65	+150	

(1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.

(2) Input terminals are diode-clamped to the power-supply rails. Input signals that can swing more than 0.3V beyond the supply rails should be current-limited to 10mA or less.

(3) The package thermal impedance is calculated in accordance with JESD-51.

(4) The maximum power dissipation is a function of T_{J(MAX)}, R_{θJA}, and T_A. The maximum allowable power dissipation at any ambient temperature is P_D = (T_{J(MAX)} - T_A) / R_{θJA}. All numbers apply for packages soldered directly onto a PCB.

ESD Ratings

The following ESD information is provided for handling of ESD-sensitive devices in an ESD protected area only.

SYMBOL	PARAMETER		VALUE	UNIT
V _(ESD)	Electrostatic discharge	Human-Body Model (HBM)	±4000	V
		Charged-Device Model (CDM)	±1000	V

Recommended Operating Conditions

Over operating free-air temperature range (unless otherwise noted)

SYMBOL	PARAMETER		MIN	MAX	UNIT
V _{CC}	Supply Voltage		1.8	5.5	V
T _A	Operating temperature		-40	+125	°C



Electrical Characteristics

VDD = +1.8V to +5.5V, GND = 0V, TA = -40°C to +125°C. Typical values are at VDD = +3.3V, TA = +25°C, unless otherwise noted.

PARAMETER	SYMBOL	CONDITIONS	TA	MIN ⁽²⁾	TYP ⁽³⁾	MAX ⁽²⁾	UNIT
Analog Switch							
Analog Signal Range	V _{NO} , V _{NC} V _{COM}		-40°C to +125°C	0		V+	V
On-Resistance	R _{ON}	V _{DD} = 3.0V, V _{NC} or V _{NO} = 0V to 0.4V, I _{COM} = 8mA, See Figure 1	+25°C		6	10	Ω
			-40°C to +125°C			10.5	Ω
On-Resistance Match Between Channels	ΔR _{ON}	V _{DD} = 3.0V, V _{NC} or V _{NO} = 0V to 0.4V, I _{COM} = 8mA, See Figure 1	+25°C		0.15	0.6	Ω
			-40°C to +125°C			1.6	Ω
On-Resistance Flatness	R _{FLAT(ON)}	V _{DD} = 3.0V, V _{NC} or V _{NO} = 0V to 1V, I _{COM} = 8mA, See Figure 1	+25°C		5	7	Ω
			-40°C to +125°C			8	Ω
Source Off Leakage Current	I _{NC(OFF)} , I _{NO(OFF)}	V _{DD} = 3.6V, V _{COM} = 0.3V or 3.6V, V _{NC} or V _{NO} = 0V or 3.6 V	-40°C to +125°C			1	μA
Channel On Leakage Current	I _{NC(ON)} , I _{NO(ON)}	V _{DD} = 3.6V, V _{COM} = 0.3V or 3.6V, V _{NC} or V _{NO} = 0V or 3.6 V or floating	-40°C to +125°C			1	μA
Digital Control Inputs ⁽¹⁾							
Input High Voltage	V _{IH}		-40°C to +125°C	1.6			V
Input Low Voltage	V _{IL}		-40°C to +125°C			0.5	V
Input Leakage Current	I _{IN}	V _{DD} = 3.0V, V _{SEL} = 0V or V _{DD}	-40°C to +125°C			1	μA

(1) All unused digital inputs of the device must be held at V_{IO} or GND to ensure proper device operation.

(2) Limits are 100% production tested at 25°C. Limits over the operating temperature range are ensured through correlations using statistical quality control (SQC) method.

(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration.



AC Electrical characteristics

VDD= +1.8V to +5.5V, TA=-40°C to +125°C. Typical values are at VDD=+3.3V, TA=+25°C, unless otherwise noted.

PARAMETER	SYMBOL	CONDITIONS	TA	MIN	TYP	MAX	UNIT
Dynamic Characteristics.							
Turn-On Time	t _{ON}	V _{IS} = 0.8V, R _L = 50Ω, C _L = 10pF,	+25°C		20		ns
Turn-Off Time	t _{OFF}	See Figure 2	+25°C		15		ns
Break-Before-Make Time Delay	t _{BBM}	V _{IS} = 0.8V, R _L = 50Ω, C _L = 10pF, See Figure 3	+25°C		4		ns
					0.35		
Propagation Delay	t _{PD}	R _L = 50Ω, C _L = 10pF	+25°C		0.35		ns
Off Isolation	O _{ISO}	Signal = 0dBm, R _L = 50Ω, Switch OFF, f = 250MHz, See Figure 4	+25°C		-35		dB
-3dB Bandwidth	BW	Signal = 0dBm, Switch ON, R _L = 50Ω, C _L = 5pF, See Figure 5	+25°C		550		MHz
Charge Injection Select Input to Common I/O	Q	V _G = GND, C _L = 1.0nF, R _G = 0Ω, Q = C _L × V _{OUT} , See Figure 6	+25°C		11		pC
NC, NO, COM ON Capacitance	C _{ON}		+25°C		7		pF
Power Requirements.							
Power Supply Range	V ₊		-40°C to +125°C	1.8		5.5	V
Power Supply Current	I ₊	V _{DD} = 3.0V, V _{SEL} = 0V or V _{DD}	-40°C to +125°C			1	μA

(1) All unused digital inputs of the device must be held at V_{IO} or GND to ensure proper device operation.

(2) Limits are 100% production tested at 25°C. Limits over the operating temperature range are ensured through correlations using statistical quality control (SQC) method.

(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration.



RSM

www.raystar-tek.com

RS3SW2157

Low Voltage Dual SPDT Analog Switch

Parameter Measurement Information




Figure 1、ON-State Resistance (R_{on})





Figure 2、Turn-On (t_{ON}) and Turn-Off Time (t_{OFF})





RSM

www.raystar-tek.com

RS3SW2157

Low Voltage Dual SPDT Analog Switch

Figure 3、 Break-Before-Make Time (t_{BBM})




Figure 4. OFF Isolation (O_{ISO})




Figure 5、 Bandwidth (BW)




Figure 6、 Charge Injection (Q)

**RSM**



www.raystar-tek.com

RS3SW2157



Low Voltage Dual SPDT Analog Switch

Package Information

SOT23-6



SYMBOL	MIN	NOM	MAX
A	—	—	1.25
A1	0	—	0.15
A2	1.00	1.10	1.20
A3	0.60	0.65	0.70
b	0.34	—	0.45
b1	0.34	0.38	0.41
c	0.12	—	0.20
c1	0.12	0.15	0.16
D	2.826	2.926	3.026
E	2.60	2.80	3.00
E1	1.526	1.626	1.700
e	0.90	0.95	1.00
e1	1.80	1.90	2.00
L	0.30	0.40	0.60
L1		0.59REF	
L2		0.25BSC	
R	0.05	—	0.20
R1	0.05	—	0.20
θ	0°	—	8°
θ 1	8°	10°	12°
θ 2	10°	12°	14°

**Note:**

- 1.All dimensions are in mm. Angles in degrees.
- 2.Refer Jedec MO-187.
- 3.Dimensions exclude burrs, mold flash or protrusions.

SOT23-6L POD Rev:0
Raystar Microelectronics Technology Inc.

**RSM**

www.raystar-tek.com

RS3SW2157Low Voltage Dual SPDT Analog Switch

Revision History

Revision	Description	DATE
V1.0	Initial Release	2025/06/30
V1.1	1.Update some parameters 2.Delete SC70-6 package 3.Modify the name of pin 6 from IN to SEL	2025/09/15