




## Features

- Operating Frequency: 0MHz~200 MHz
- Low noise: <50fs rms
- low skew: < 50ps
- Fast rise/fall time: 1.0ns typ.
- Propagation delay: 2.5ns typ.
- Industrial temperature (−40°C to 125°C)
- 3.3V/2.5V/1.8V power supply
- AEC-Q100 qualified, Automotive Grade 1 support; PPAP capable, and manufactured in IATF 16949 certified facilities
- Packaging (Pb-free & Green available)

## Applications

- 10/100/1000 Mbps Ethernet
- Automotive LiDAR
- ADAS

## Block Diagram



**Figure 1 Block Diagram**

## Description

Raystar’s RS304Q are low-skew, low- noise, high speed clock buffers and are ideal for computing, networking, and communication applications. Application examples include PCI(X) clock buffers in servers and workstations, PCI(X) Storage Area Network (SAN), and RAID controllers. They are used for networking and communications applications requiring 80 MHz for 10/100 Mbps Ethernet and 125 MHz for Gigabit networking clocks. To reduce EMI emission and power consumption, all outputs can be disabled to Low-state by asserting a low signal to the OE (Output Enable) pin. RS304 output impedance is 50 ohms.

## Order Information

Part Number	Package	Description
RS304QWE	8-Pin SOIC	4.9mmx6mm
RS304QUE	8-Pin MSOP	3.2mmx5.15mm
RS304QZAE	8-Pin DFN8	2mmx2mm

### Notes

- [1] E = Pb-free and Green



## Pin Configuration



Table 1 Function table

INPUT		OUTPUT
CLK_IN	OE	Y[0:3]
X	L	L
L	H	L
H	H	H

## Pin Description

Pin name	Pin No.	Type	Description
CLK_IN	1	Input	Clock input
OE	2	Input	Active High Output Enable. Y[0:3] outputs will be Low Level when OE is low
Y[0:3]	3,5,7,8	Output	LVCMOS level outputs
GND	4	Ground	Ground
VDD	6	Power	3.3V/2.5V/1.8V Power Supply



## Absolute Maximum Ratings

Parameter	Range
Supply Voltage (VDD)	-0.0V to +6.5V
Input Voltage	-0.5V to VDD+0.5V
Operating Temperature	-40°C to +125°C
Storage Temperature	-65°C to +150°C
Junction Temperature	150°C
Input ESD MIL- 883, method 3015, human body model	2KV

## Recommended Operating Conditions

Symbol	Parameter	MIN	MAX	Unit
VDD	I/O Supply, Analog Core Supply	1.71	3.63	V
TA	Ambient Temperature	-40	125	° C

## DC Electrical Characteristics

(TA = -40~125°C, VCC = 3.3V ±10%, 2.5V ±10%, 1.8V ±5%)

Symbol	Parameter	Conditions	MIN	TYP	MAX	Unit
V <sub>IL</sub>	Low Input Voltage				0.8	V
V <sub>IH</sub>	High Input Voltage		0.6*VDD			
I <sub>IL</sub>	Low Input Current	V <sub>IN</sub> = 0V			-5	μA
I <sub>IH</sub>	High Input Current	V <sub>IN</sub> = VDD			5	
V <sub>OL</sub>	Low Output Voltage	I <sub>OL</sub> = 12mA			0.25*VDD	V
V <sub>OH</sub>	High Output Voltage	I <sub>OH</sub> = - 12mA	0.7*VDD			
C <sub>O</sub>	Output Capacitance			3	7	pF
C <sub>I</sub>	Input Capacitance			3	5	
I <sub>DD</sub>	Supply Current	CL = 15pF/100MHz VDD=3.3V		32		mA
		CL = 15pF/100MHz VDD=2.5V		26		
		CL = 15pF/100MHz VDD=1.8V		20		
Z <sub>O</sub>	Output Impedance			50		Ω
L	Pin Inductance				7	nH



## AC Characteristics

(TA = -40~125°C, VCC = 3.3V ±10%, 2.5V ±10%, 1.8V ±5%, 15pF/100MHz)


Symbol	Parameter	Conditions	MIN	TYP	MAX	Unit
F <sub>IN</sub>	Input frequency		0		200	MHz
T <sub>PLH</sub>	Low-to-high propagation delay	CLK_IN to Y[0-3] rising edges @ 1.5V	1.0	1.7	3.0	ns
		CLK_IN to Y[0-3] rising edges @ 1.25V	1.0	2.0	3.2	
		CLK_IN to Y[0-3] rising edges @ 0.9V	1.0	2.5	3.5	
T <sub>PHL</sub>	High-to-low propagation delay	CLK_IN to Y[0-3] falling edges @ 1.5V	1.0	1.7	3.0	
		CLK_IN to Y[0-3] falling edges @ 1.25V	1.0	2.0	3.2	
		CLK_IN to Y[0-3] falling edges @ 0.9V	1.0	2.5	3.5	
T <sub>SK(O)</sub>	Output skew	@ VDD/2			100	ps
T <sub>SK(P)</sub>	Pulse skew	@ VDD/2			300	
T <sub>SK(T)</sub>	Package skew(1)	@ VDD/2			500	
T <sub>R</sub> , T <sub>F</sub>	Rise, Fall time	20%~80% VDD=3.3V		0.7	1.4	ns
		20%~80% VDD=2.5V		1	2	
		20%~80% VDD=1.8V		1.5	3	
T <sub>PZL</sub> , T <sub>PZH</sub>	Output enable time				5	
T <sub>PLZ</sub> , T <sub>PHZ</sub>	Output disable time				10	
T <sub>DC</sub>	Output duty cycle	t <sub>DC</sub> = t <sub>H</sub> /t <sub>C</sub> Y, t <sub>H</sub> = High Pulse Width	45		55	

### Note:


1. Identical traces, loads, power supply.
2. Maximum Output Skew is 100ps when frequency is below 125MHz with 10pF loading.




## Parameter Measurement Information




Test Load Circuit



Application Load With 50-Ω Termination



Application Load With Termination




Rise and Fall Time



## Power Supply Recommendations

High-performance clock buffers can be sensitive to noise on the power supply, which may dramatically increase the additive jitter of the buffer. Thus, it is essential to manage any excessive noise from the system power supply, especially for applications where the jitter and phase noise performance is critical.

Filter capacitors are used to eliminate the low-frequency noise from the power supply, where the bypass capacitors provide the very low impedance path for high-frequency noise and guard the power supply system against induced fluctuations. These bypass capacitors also provide instantaneous current surges as required by the device and should have low equivalent series resistance (ESR). To properly bypass the supply, the decoupling capacitors must be placed very close to the power-supply terminals, be connected directly to the ground plane, and laid out with short loops to minimize inductance. It is recommended adding as many high-frequency (for example, 0.1  $\mu\text{F}$ ) bypass capacitors, as there are supply terminals in the package. We recommends, but does not require, inserting a ferrite bead between the board power supply and the chip power supply that isolates the high-frequency switching noises generated by the clock buffer; these beads prevent the switching noise from leaking into the board supply. It is imperative to choose an appropriate ferrite bead with very low DC resistance to provide adequate isolation between the board supply and the chip supply, as well as to maintain a voltage at the supply terminals that is greater than the minimum voltage required for proper operation.





## Package Information

### 8-Pin SOIC (W)

SYMBOLS	MIN.	NOM.	MAX.
A	—	—	1.75
A1	0.10	—	0.25
A2	1.25	—	—
b	0.31	—	0.51
c	0.10	—	0.25
D	4.80	4.90	5.00
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	1.27 BSC		
L	0.40	—	1.27
h	0.25	—	0.50
$\theta^\circ$	0	—	8

Recommended Land Pattern

**SOP08 POD**


**Raystar Microelectronics Technology Inc.**

**Note:**


- 1.All dimensions are in mm. Angels in degrees.
- 2.Dimensions exclude burrs, mold flash or protrusions.
- 3.Refer Jeduc MS-012
4. Recommended land pattern is for reference only.



**8-Pin MSOP (U)**



PKG DIMENSIONS(MM)		
SYMBOL	Min.	Max.
A	--	1.10
A1	0.00	0.15
A2	0.75	0.95
b	0.22	0.38
c	0.08	0.23
D	2.80	3.20
E	4.65	5.15
E1	2.80	3.20
e	0.65 BSC	
L	0.40	0.80
L1	0.95 REF	
θ	0°	8°



**Note:**

- 1.All dimensions are in mm. Angels in degrees.
- 2.Refer Jedec MO-187
- 3.Dimensions exclude burrs, mold flash or protrusions.




MSOP08 POD Rev.0

**Raystar Microelectronics Technology Inc.**



**8-Pin DFN8 (ZA)**



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0	0.02	0.05
b	0.18	0.25	0.30
b1	0.18REF		
c	0.203REF		
D	1.90	2.00	2.10
e	0.50BSC		
Nd	1.50BSC		
E	1.90	2.00	2.10
L	0.45	0.50	0.55
h	0.10	0.15	0.20

**Notes:**

1. All dimensions are in mm. Angles in degrees.
2. Refer JEDEC MO-229
3. Dimensions exclude burrs, mold flash or protrusions.





## Revision History

Revision	Description	Date
V0.9	Preliminary	2025/05/28
V1.0	Initial release	2025/07/16
V1.1	Errata and corrections	2025/09/05